

PROVISIONAL LAYOUT AND SPECIFICATIONS



LENGTH



10.68 m

BEAM FOLDED



3.70 m

MAX. CREW



5-7 people

TRAILABLE



NO

MAX. SPEED



22 knots

CE-CATEGORY



A

	TOURING	PERFORMANCE
Length overall centre hull incl. fixed bowsprit	10.68	10.68 m
Length waterline centre hull	10.07	10.07 m
Length folded	12.80	12.80 m
Beam sailing	8.10	8.10 m
Beam folded	3.70	3.70 m
Draft board up	0.55	0.55 m
Draft board down	1.85	1.85 m
Weight of standard dry boat, ready to sail, excl. extra equipment	3.900	3.900 kg
Max total weight, excl. crew	5.500	5.500 kg
Water capacity (cold), standard	120	120 Litres
Water capacity (hot), optional	15	15 Litres
Holding tank	80	80 litres
Fuel tank, diesel	70	70 litres
Engine, standard	30/21.3	30/21.3 Hp/kW
Engine, optional	40/29.4	40/29.4 Hp/kW
Mast section, carbon	15.20	17.20 m
Mainsail	50	60 m ²
Furling genoa	27	30 m ²
Furling Code-0	50	60 m ²
Gennaker	100	120 m ²
Bowsprit fixed length	0.80	0.80 m
Unsinkable	Yes	Yes

All descriptions, illustrations etc. are indications only. The boats are shown with options.
Quorning Boats ApS reserve all rights to modify or improve the specifications without prior notice

Designed by
Olsen Design & Quorning Boats, Denmark